



## DECLARATION OF PERFORMANCE

No: KAGR\_004

1. Unique identification code of the product-type: **AQUAPANEL® Cement Board SkyLite SL\_8,0\_902**
2. Intended use/es: **AQUAPANEL® Cement Board 8 mm (hydrophobic) for use in suspended ceilings in interior and exterior applications.**
3. Manufacturer: **Knauf Aquapanel ABEE, 2nd Industrial Zone of Volos, GR-37500 Volos**  
Tel.: +30 24250 24340, Fax: +30 24250 24342, E-Mail: [aquapanel.info@knauf.com](mailto:aquapanel.info@knauf.com)
4. Authorised representative: not applicable
5. System/s of AVCP: **System 3** (reaction to fire), **System 4** (all other product characteristics)
6. a) Harmonised standard: not applicable  
Notified body/ies: not applicable
6. b) European Assessment Document / European Technical Assessment / Technical  
Assessment Body: **ETA-13/0608, Deutsches Institut für Bautechnik, 19.06.2019**  
Notified body/ies: MPA Nordrhein-Westfalen (0432)
7. Declared performance/s:

Essential Characteristics	Performance
<b>Safety in case of fire (BWR 2)</b>	
Reaction to fire	Class A1 according to EN 13501-1:2019-05
<b>Hygiene, health, and environment (BWR 3) / Content, emission and/or release</b>	
Substance(s) classified as EU-cat. Carc. 1A/1B	The product does not contain these dangerous substances.
Substance(s) classified as EU-cat. Muta. 1A/1B	
Substance(s) classified as EU-cat. Acute Tox. 1, 2 and/or 3; substance(s) classified as EU-cat. Repr. 1A/1B; substance(s) classified as EU-cat. STOT SE 1 and/or STOT RE 1	
<b>Safety and accessibility in use (BWR 4)</b>	
Thickness	e = 8 mm ± 0,8 mm
Dimensions (length and width)	Annex C
Straightness of edges	0,1 % = Level I according to EN 12467
Squareness of edges	2 mm/m = Level I according to EN 12467
Density	$\rho_{\text{mean}} = 1230 \pm 175 \text{ kg/m}^3$
Moisture content	H ≤ 13 % by mass
<b>Essential Characteristics</b>	
<b>Performance</b>	
<b>Safety and accessibility in use (BWR 4)</b>	
Water permeability	Passed

**AQUAPANEL®**



Dimensional stability – length	$\delta_{65,85} = 0,38 \text{ mm/m}$ , $\delta_{65,30} = -0,32 \text{ mm/m}$	
Dimensional stability – thickness	$\delta_{65,85} = 0,3 \%$ , $\delta_{65,30} = -0,3 \%$	
Bending strength	$f_{m,0,k} = 6.9 \text{ N/mm}^2$ , $f_{m,90,k} = 10.9 \text{ N/mm}^2$	
Bending modulus of elasticity	$E_{m,0,\text{mean}}$ , 800 MPa $E_{m,90,\text{mean}}$ 1750 MPa	
Pull through resistance AQUAPANEL Maxi Screw	Type SN (Annex A1)	$f_{\text{head},k} = 2.8 \text{ N/mm}^2$
	Type SB (Annex A2)	$f_{\text{head},k} = 2.8 \text{ N/mm}^2$
Pull through resistance AQUAPANEL Rustproofed screw	Type SN (Annex A3)	$f_{\text{head},k} = 2.8 \text{ N/mm}^2$
	Type SB (Annex A4)	$f_{\text{head},k} = 2.8 \text{ N/mm}^2$
Impact resistance	$IR_{\text{mean}} = 12,5 \text{ mm/m}$	
Water adsorption	$w_a = \text{No Performance assessed}$	
Freeze-thaw resistance for category B	$R_{L,FTC} = 0,94$	
Heat-rain resistance for category B	Passed	
Warm water resistance for category B	$R_{L,ww} = 0,82$	
Soak-dry resistance for category B	$R_{L,SD} = 1,0$	
Durability of metal parts	Annex B1	
<b>Energy economy and heat retention (BWR 6)</b>		
Thermal conductivity	$\lambda_{10,\text{tr}} = 0.36 \text{ W/(m.K)}$	
Air permeability	The "AQUAPANEL Cement Board SkyLite" is not permeable to air.	

8. Appropriate Technical Documentation and/or Specific Technical Documentation: not applicable

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Claus Ripken  
General Manager

Iserlohn, 18.10.2021

28.5.2014 L 159/43 Official Journal of the European Union EN



Be certain, choose AQUAPANEL®  
Rev. 01, 18.10.2021